



Antek Madison Plastics Corp
100 Finchdene Sq
Scarborough, Ontario M1X 1C1
Phone: (416) 321-1170
Fax: (416) 321-2809

10/29/24

TECHNICAL DATA SHEET

PP 20M NO BREAK NATURAL PELLETS - FDA

NOMINAL PHYSICAL PROPERTIES	ENGLISH	SI	METHOD
Density	0.9 g/cm ³	900 kg/m ³	ASTM D1505
Melt Flow Rate	20 g/10 min	20 g/10 min	ASTM D1238
Flexural modulus (1% secant) at 1.27 mm/min	160,000 psi	1103 Mpa	
Tensile Strength at Yield	3,500 psi	24.2 MPa	ASTM D638
Yield Elongation	6 %	6 %	ASTM D638
Notched Izod Impact Strength at 73°F/23°C	≥10 ft-lb/in	≥534 J/m	ASTM D256

Antek Madison Plastics Corp.

Laboratory Department

Data Properties Disclaimer: Antek Madison Plastics Corp shall not be responsible for the applicability, or the accuracy of the information contained herein, or the suitability of the products described herein for any particular purpose. It is the ultimate responsibility of the user to ensure that the product is suited, and the information is applicable to the user's specific application. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made with respect to the products described herein or with respect to the use of the products described herein.